

# Sediment pore water and solid phase geochemical analyses from samples collected on R/V Savannah cruise SAV-17-15 in the Gulf of Mexico during July and August 2017

**Website:** <https://www.bco-dmo.org/dataset/806105>

**Data Type:** Cruise Results

**Version:** 1

**Version Date:** 2020-03-17

## Project

» [Source, Composition, and Stability of Soluble Iron Fluxing from Continental Margin Sediments](#) (Soluble Fe Fluxing)

Contributors	Affiliation	Role
<a href="#">Taillefert, Martial</a>	Georgia Institute of Technology (GA Tech)	Principal Investigator
<a href="#">Rauch, Shannon</a>	Woods Hole Oceanographic Institution (WHOI BCO-DMO)	BCO-DMO Data Manager

## Abstract

Sediment pore water and solid phase geochemical analyses from samples collected on R/V Savannah cruise SAV-17-15 in the Gulf of Mexico during July and August 2017.

---

## Table of Contents

- [Coverage](#)
  - [Dataset Description](#)
    - [Methods & Sampling](#)
    - [Data Processing Description](#)
  - [Data Files](#)
  - [Related Publications](#)
  - [Parameters](#)
  - [Instruments](#)
  - [Deployments](#)
  - [Project Information](#)
  - [Funding](#)
- 

## Coverage

**Spatial Extent:** N:28.9476 E:-88.8484 S:28.2007 W:-91.3362

**Temporal Extent:** 2017-07-26 - 2017-08-06

## Methods & Sampling

Sediments were collected and profiled immediately with voltammetric Hg/Au microelectrodes deployed on a computer-controlled micromanipulator (Beckler et al., 2016). Sediment pore waters were then extracted from the same core and either preserved until analysis or analyzed immediately onboard ship. Sampling and analyses were conducted immediately after sediment collection to minimize artifacts from exposure to the atmosphere.

Sediment cores were obtained by a MC-800 multi-corer and profiled within 30 minutes with voltammetric Hg/Au microelectrodes deployed on a computer-controlled micromanipulator. After profiling, sediments were immediately sliced under N<sub>2</sub> atmosphere and pore waters extracted by centrifugation at 3000 rpm under N<sub>2</sub> atmosphere. Finally, pore waters were immediately filtered (0.2 µM PSE Puradisc syringe filters, Whatman) under N<sub>2</sub> atmosphere and either preserved at -20C until analysis (Br<sup>-</sup>, NO<sub>2</sub><sup>-</sup>, NO<sub>3</sub><sup>-</sup>, SO<sub>4</sub><sup>2-</sup>), preserved at 4C after acidification (NH<sub>4</sub><sup>+</sup>), dispensed directly into reagents for analysis (Fe(II), Fed, Mnd, SPO<sub>4</sub><sup>3-</sup>), or analyzed immediately (DIC, TA). Br<sup>-</sup>, NO<sub>2</sub><sup>-</sup>, NO<sub>3</sub><sup>-</sup>, and SO<sub>4</sub><sup>2-</sup> were measured by non-suppressed HPLC with UV detection (Beckler et al., 2014). NH<sub>4</sub><sup>+</sup> was measured spectrophotometrically by the indophenol blue method (Strickland

and Parsons, 1972), Fe and Fe(II) were measured by the ferrozine method after addition or not of hydroxylamine (Stookey, 1970). Mn was measured by the porphyrin kinetic spectrophotometric method (Madison et al., 2011) modified to account for dissolved Fe(II) interferences (Owings et al., 2020).  $\text{SPO}_4^{3-}$  was measured spectrophotometrically using the molybdate-blue method after natural color correction to avoid interferences from dissolved silica and sulfides (Murphy and Riley, 1962). DIC was measured by flow injection analysis with conductivity detection after spiking samples with 10 mM  $\text{ZnCl}_2$  to prevent dissolved sulfide interferences (Hall and Aller, 1992). Finally, TA was measured by acid titration in an open-cell with continuous pH measurements (Dickson et al., 2007; Rassmann et al., 2016). All errors reported for the electrochemical measurements represent the standard deviation of at least triplicate measurements. Errors of all other parameters represent the analytical error propagated from calibration curves, dilution, and instrumental drift.

**Problem report:** Some of the data are missing because pore water volumes were too low to make all the measurements.

## Data Processing Description

Chromatographic data were processed using Voltint (Bristow and Taillefert, 2008), a Matlab™-based software developed for these applications. Spectrophotometric measurements were processed manually.

### BCO-DMO Processing:

- added date column using original year, month, and day columns.

[ [table of contents](#) | [back to top](#) ]

---

## Data Files

File
<b>porewater_SAV17-15.csv</b> (Comma Separated Values (.csv), 35.93 KB) MD5:b535a05764c297d3069d7d42edee29fa Primary data file for dataset ID 806105

[ [table of contents](#) | [back to top](#) ]

---

## Related Publications

Beckler, J. S., Kiriazis, N., Rabouille, C., Stewart, F. J., & Taillefert, M. (2016). Importance of microbial iron reduction in deep sediments of river-dominated continental-margins. *Marine Chemistry*, 178, 22–34.

doi:[10.1016/j.marchem.2015.12.003](https://doi.org/10.1016/j.marchem.2015.12.003)

*Methods*

Beckler, J. S., Nuzzio, D. B., & Taillefert, M. (2014). Development of single-step liquid chromatography methods with ultraviolet detection for the measurement of inorganic anions in marine waters. *Limnology and Oceanography: Methods*, 12(8), 563–576. doi:[10.4319/lom.2014.12.563](https://doi.org/10.4319/lom.2014.12.563)

*Methods*

Bristow, G., & Taillefert, M. (2008). VOLTINT: A Matlab®-based program for semi-automated processing of geochemical data acquired by voltammetry. *Computers & Geosciences*, 34(2), 153–162.

doi:[10.1016/j.cageo.2007.01.005](https://doi.org/10.1016/j.cageo.2007.01.005)

*Methods*

Dickson, A.G., Sabine, C.L. and Christian, J.R. (Eds.) 2007. Guide to best practices for ocean CO<sub>2</sub> measurements. PICES Special Publication 3, 191 pp. ISBN: 1-897176-07-4. URL:

[https://www.nodc.noaa.gov/ocads/oceans/Handbook\\_2007.html](https://www.nodc.noaa.gov/ocads/oceans/Handbook_2007.html) <https://hdl.handle.net/11329/249>

*Methods*

Eitel, E. M., Owings, S. M., Belli, K. M., Beckler, J. S., Williams, A., Fields, B. P., ... Taillefert, M. (2020). Variations in sediment production of dissolved iron across a continental margin not dominated by major upwelling or riverine inputs. *Marine Chemistry*, 220, 103750. doi:[10.1016/j.marchem.2020.103750](https://doi.org/10.1016/j.marchem.2020.103750)

*Results*

Hall, P. . J., & Aller, R. C. (1992). Rapid, small-volume, flow injection analysis for total CO<sub>2</sub>, and NH<sub>4</sub><sup>+</sup> in marine and freshwaters. *Limnology and Oceanography*, 37(5), 1113–1119. doi:[10.4319/lo.1992.37.5.1113](https://doi.org/10.4319/lo.1992.37.5.1113)

*Methods*

Madison, A. S., Tebo, B. M., & Luther, G. W. (2011). Simultaneous determination of soluble manganese(III), manganese(II) and total manganese in natural (pore)waters. *Talanta*, 84(2), 374–381.

doi:[10.1016/j.talanta.2011.01.025](https://doi.org/10.1016/j.talanta.2011.01.025)

*Methods*

Murphy, J., & Riley, J. P. (1962). A modified single solution method for the determination of phosphate in natural waters. *Analytica Chimica Acta*, 27, 31–36. doi:[10.1016/s0003-2670\(00\)88444-5](https://doi.org/10.1016/s0003-2670(00)88444-5)

*Methods*

Rassmann, J., Lansard, B., Pozzato, L., & Rabouille, C. (2016). Carbonate chemistry in sediment porewaters of the Rhone River delta driven by early diagenesis (northwestern Mediterranean). *Biogeosciences*, 13(18), 5379–5394. doi:[10.5194/bg-13-5379-2016](https://doi.org/10.5194/bg-13-5379-2016)

*Methods*

Stookey, L. L. (1970). Ferrozine---a new spectrophotometric reagent for iron. *Analytical Chemistry*, 42(7), 779–781. doi:[10.1021/ac60289a016](https://doi.org/10.1021/ac60289a016)

*Methods*

Strickland, J. D. H. and Parsons, T. R. (1972). *A Practical Hand Book of Seawater Analysis*. Fisheries Research Board of Canada Bulletin 157, 2nd Edition, 310 p.

*Methods*

[ [table of contents](#) | [back to top](#) ]

---

## Parameters

Parameter	Description	Units
Year	Year	unitless
Month	Month	unitless
Day	Day	unitless
Collection_Type	Type of collection	unitless
Station	Station number	unitless
Lon	Longitude	decimal degrees East
Lat	Latitude	decimal degrees North
sample_ID	Sample ID number	unitless
Sediment_depth	Sediment depth	centimeters (cm)
Fe_II	Dissolved ferrous iron	micromolar (uM)

sdFe_II	Standard deviation of Fe_II	micromolar (uM)
Fed	Total dissolved iron	micromolar (uM)
sdFed	Standard deviation of Fed	micromolar (uM)
Fe_III_d	Dissolved ferric iron	micromolar (uM)
sdFe_III_d	Standard deviation of Fe_III_d	micromolar (uM)
DIC	Dissolved inorganic carbon	millimolar (mM)
sdDIC	Standard deviation of DIC	millimolar (mM)
PO4	Dissolved orthophosphate	micromolar (uM)
sdPO4	Standard deviation of PO4	micromolar (uM)
Mnd	Total dissolved manganese	micromolar (uM)
sdMnd	Standard deviation of Mnd	micromolar (uM)
NH4	Dissolved ammonium	micromolar (uM)
sdNH4	Standard deviation of NH4	micromolar (uM)
NO2	Dissolved nitrite	micromolar (uM)
sdNO2	Standard deviation of NO2	micromolar (uM)
Br	Dissolved bromide	micromolar (uM)
sdBr	Standard deviation of Br	micromolar (uM)
NO3	Dissolved nitrate	micromolar (uM)
sdNO3	Standard deviation of NO3	micromolar (uM)

Cl	Dissolved chloride	millimolar (mM)
sdCl	Standard deviation of Cl	millimolar (mM)
SO42	Sulfate	millimolar (mM)
sdSO42	Standard deviation of SO42	millimolar (mM)
TA	Total Alkalinity	millimolar (mM)
sdTA	Standard deviation of TA	millimolar (mM)
date	Date; format: yyyy-mm-dd	unitless

[ [table of contents](#) | [back to top](#) ]

## Instruments

<b>Dataset-specific Instrument Name</b>	Flow Injection Analysis
<b>Generic Instrument Name</b>	Flow Injection Analyzer
<b>Dataset-specific Description</b>	Flow Injection Analysis with peristaltic pump (Gilson), conductivity detector (Fisher Scientific), and integrator with LC-100 software (Analytical Systems, Inc.)
<b>Generic Instrument Description</b>	An instrument that performs flow injection analysis. Flow injection analysis (FIA) is an approach to chemical analysis that is accomplished by injecting a plug of sample into a flowing carrier stream. FIA is an automated method in which a sample is injected into a continuous flow of a carrier solution that mixes with other continuously flowing solutions before reaching a detector. Precision is dramatically increased when FIA is used instead of manual injections and as a result very specific FIA systems have been developed for a wide array of analytical techniques.

<b>Dataset-specific Instrument Name</b>	HPLC
<b>Generic Instrument Name</b>	High-Performance Liquid Chromatograph
<b>Dataset-specific Description</b>	Br <sup>-</sup> , NO <sub>2</sub> <sup>-</sup> , NO <sub>3</sub> <sup>-</sup> , and SO <sub>4</sub> <sup>2-</sup> were measured by non-suppressed HPLC with UV detection
<b>Generic Instrument Description</b>	A High-performance liquid chromatograph (HPLC) is a type of liquid chromatography used to separate compounds that are dissolved in solution. HPLC instruments consist of a reservoir of the mobile phase, a pump, an injector, a separation column, and a detector. Compounds are separated by high pressure pumping of the sample mixture onto a column packed with microspheres coated with the stationary phase. The different components in the mixture pass through the column at different rates due to differences in their partitioning behavior between the mobile liquid phase and the stationary phase.

<b>Dataset-specific Instrument Name</b>	MC-800 multi-corer
<b>Generic Instrument Name</b>	Multi Corer
<b>Dataset-specific Description</b>	Sediment cores were obtained by a MC-800 multi-corer.
<b>Generic Instrument Description</b>	The Multi Corer is a benthic coring device used to collect multiple, simultaneous, undisturbed sediment/water samples from the seafloor. Multiple coring tubes with varying sampling capacity depending on tube dimensions are mounted in a frame designed to sample the deep ocean seafloor. For more information, see Barnett et al. (1984) in Oceanologica Acta, 7, pp. 399-408.

<b>Dataset-specific Instrument Name</b>	spectrophotometer
<b>Generic Instrument Name</b>	Spectrophotometer
<b>Dataset-specific Description</b>	NH <sub>4</sub> <sup>+</sup> was measured spectrophotometrically
<b>Generic Instrument Description</b>	An instrument used to measure the relative absorption of electromagnetic radiation of different wavelengths in the near infra-red, visible and ultraviolet wavebands by samples.

[ [table of contents](#) | [back to top](#) ]

## Deployments

SAV-17-15

<b>Website</b>	<a href="https://www.bco-dmo.org/deployment/806108">https://www.bco-dmo.org/deployment/806108</a>
<b>Platform</b>	R/V Savannah
<b>Start Date</b>	2017-07-19
<b>End Date</b>	2017-08-13
<b>Description</b>	More cruise information from the Rolling Deck to Repository (R2R): <a href="https://www.rvdata.us/search/cruise/SAV-17-15">https://www.rvdata.us/search/cruise/SAV-17-15</a>

[ [table of contents](#) | [back to top](#) ]

---

## Project Information

### Source, Composition, and Stability of Soluble Iron Fluxing from Continental Margin Sediments (Soluble Fe Fluxing)

**Coverage:** Northern South Atlantic Bight (Cape Lookout, NC) and Northern Gulf of Mexico

#### *NSF Award Abstract:*

Iron is a limiting nutrient in the world's oceans and plays a key role in regulating the growth of phytoplankton. The main sources of iron to the open ocean are the atmosphere, through wind-blown terrestrial dust, and the seafloor, through input from continental shelf sediments. While atmospheric inputs have been well-studied, the oceanic input of iron from sediments has only sparsely been measured and, as a result, the relative importance of the sediment-derived iron to the iron pool and, ultimately, primary productivity in the oceans is poorly understood. In this study, researchers will examine the chemical properties of sediment-derived iron in the oceans to assess its contribution to the iron used by phytoplankton. Results from this study will further our understanding of iron inputs to the ocean and their importance to ocean primary productivity. The project will contribute to the training of graduate students, as well as provide educational opportunities such as a day at sea for undergraduate students in engineering and physical science.

The atmosphere and continental margin sediments are the main source of the limiting nutrient iron (Fe) to the open ocean. Yet, the chemical form of iron from sediments has not been well examined and only quantified as reduced iron or the dissolved iron passing through 0.45  $\mu\text{m}$  filters. The kinetics of iron oxygenation suggests it should precipitate rapidly in the overlying waters, challenging the view that sediments are important sources of iron for primary production. To establish whether the flux of iron from sediments has important implications for primary productivity, possibly rivaling atmospheric inputs, it is necessary to demonstrate that ferric iron originating in sediments is under the form of stable iron species with potential for a high residence time in the water column. The overall objective of this project is to test the hypotheses that iron fluxing across the sediment-water interface in continental margin sediments is dissolved under the form of organic-Fe(III) complexes and that the magnitude of the iron flux is influenced by the redox conditions in the overlying waters, the composition of the complexes, and the biogeochemical processes in the underlying sediments. To test these hypotheses, the flux and speciation of dissolved Fe(III) will be quantified in the sediments of the Carolina depocenter and the Gulf of Mexico, and the biogeochemical processes regulating the production and the flux of iron as a function of the redox regime of the environment will be determined using in situ measurements and state-of-the-art voltammetric and chromatographic techniques.

[ [table of contents](#) | [back to top](#) ]

---

## Funding

Funding Source	Award
<a href="#">NSF Division of Ocean Sciences (NSF OCE)</a>	<a href="#">OCE-1438648</a>

[ [table of contents](#) | [back to top](#) ]