



## **MICRO SURFACE ACQUISITION SYSTEM (MICROSAS)**

---

The MicroSAS remote sensing system is designed for above-water measurements of ocean colour using Satlantic's new digital optical sensors. The system consists of two radiance sensors and one irradiance sensor. One radiance sensor is pointed to the ocean to measure the sea surface signal; the other is pointed to the sky to provide information necessary for surface glint correction of the data collected by the first sensor. The irradiance sensor is used to monitor the downwelling light field and is required for computing remote sensing reflectance.

The MicroSAS can be mounted on a variety of vessels for continuous monitoring of ocean colour along the ship's track, on towers or other platforms for time series observations, or the system can be used for airborne remote sensing of ocean colour. It is small, light and compact, which makes it very easy to deploy.



The spectral water-leaving radiance and remote sensing reflectance data obtained from MicroSAS are used to derive the concentrations of sea-water constituents, such as dissolved organic matter, suspended sediments, and chlorophyll concentration in the surface layer. Since chlorophyll is an indicator of algal biomass, this information is used to estimate phytoplankton abundance and marine productivity, to detect phytoplankton blooms, and to monitor organic pollution through its influence on blooms. The MicroSAS also provides valuable surface truth for calibration and validation of satellite ocean colour products. If surface water samples are taken simultaneously with MicroSAS measurements, the combined dataset can be used for bio-optical modeling.

For additional information about the MicroSAS, please contact [info@satlantic.com](mailto:info@satlantic.com) or visit [www.satlantic.com/sas](http://www.satlantic.com/sas).



**YOUR PARTNER IN RESEARCH**

**MICROSAS**

**MICROSAS SPECIFICATIONS**

---

**SPATIAL CHARACTERISTICS**

Irradiance field of view:	Cosine response (spectrally corrected)
Radiance field of view:	3.3°
Collector area:	86.0 mm <sup>2</sup>
Detectors:	Custom 17 mm <sup>2</sup> silicon photodiodes

**SPECTRAL CHARACTERISTICS**

Wavelength range:	300-865 nm
Number of channels:	7 water radiance (Lt) 7 irradiance (Es) 7 sky radiance (Li)
Spectral bandwidth:	10 or 20 nm
Filter type:	IAD (ion assisted deposition) Custom low fluorescence



The MicroSAS can be mounted on ships of opportunity, small planes and helicopters.

**OPTICAL CHARACTERISTICS**

Out of band rejection:	10 <sup>-6</sup>
Cosine response:	3% from 0-60°; 10% from 60-85°
Typical saturation:	20 μWcm <sup>-2</sup> nm <sup>-1</sup> sr <sup>-1</sup> (Lt) 300 μWcm <sup>-2</sup> nm <sup>-1</sup> (Es) 60 μWcm <sup>-2</sup> nm <sup>-1</sup> sr <sup>-1</sup> (Li)
Typical NER:	0.2 x 10 <sup>-3</sup> μWcm <sup>-2</sup> nm <sup>-1</sup> sr <sup>-1</sup> (Lt)
Typical NEI:	2.5 x 10 <sup>-3</sup> μWcm <sup>-2</sup> nm <sup>-1</sup> (Es)
Typical NER:	0.5 x 10 <sup>-3</sup> μWcm <sup>-2</sup> nm <sup>-1</sup> sr <sup>-1</sup> (Li)



MicroSAS applications also include fixed ocean platforms.

**SYSTEM ELECTRONICS**

System data rate:	20 Hz
Data acquisition:	24 bit DSP A/D system
Power:	9-18 VDC at 300mA
Telemetry:	RS-422 115 Kbps
Format:	Custom binary
Optional:	Integrated GPS Garmin Integrated IR sensor

*Specifications may change without notice  
January 2008*